Form Approved OMB No. 0938-0242

ZONES

ZONE \_\_\_\_

## FIRE/SMOKE ZONE\* EVALUATION WORKSHEET FOR HEALTH CARE FACILITIES

2000 LIFE SAFETY CODE

OF

FACILITY

BUILDING

ZONE(S) EVALUATED

PROVIDER/VENDOR NO.

DATE OF SURVEY

## COMPLETE THIS WORKSHEET FOR EACH ZONE. WHERE CONDITIONS ARE THE SAME IN SEVERAL ZONES, ONE WORKSHEET CAN BE USED FOR THOSE ZONES.

- **Step 1:** Determine Occupancy Risk Parameter Factors Use Table 1.
  - A. For each Risk Parameter in Table 1, select and circle the appropriate risk factor value. Choose only one for each of the five Risk Parameters.

TABLE 1. OCCUPANCY RISK PARAMETER FACTORS								
Risk Parameters		Risk I	Factors Values					
1. Patient	Mobility Status	Mobile	Limited M	Limited Mobility		ot Mobile	Not Movable	
Mobility (M)	Risk Factor	1.0	1.6	1.6		3.2	4.5	
2. Patient Density <i>(D)</i>	No. of Patients	1–5	6–10	10		11–30	>30	
	Risk Factor	1.0	1.2	1.2		1.5	2.0	
3. Zone	Floor	1 <sup>st</sup>	2 <sup>nd</sup> or 3 <sup>rd</sup>	4 <sup>th</sup> to 6 <sup>th</sup>		7 <sup>≞</sup> and Above	Basements	
Location (L)	Risk Factor	1.1	1.2	1.4		1.6	1.6	
4. Ratio of Patients to	Patients Attendant	<u>1–2</u> 1	<u>3–5</u> 1	<u>6–10</u> 1		> <u>10</u> 1	One or More None	
Attendants (T)	Risk Factor	1.0	1.1	1.2		1.5	4.0	
5. Patient Average	Age	Under 65 Yea	65 Years and Over 1 Year and Younger					
Age (A)	Risk Factor			1.2				

Step 2: Compute Occupancy Risk Factor (F) - Use Table 2.

- A. Transfer the circled risk factor values from Table 1 to the corresponding blocks in Table 2.
- B. Compute F by multiplying the risk factor values as indicated in Table 2.

TABLE 2. OCCUPANCY RISK FACTOR CALCULATION						
OCCUPANCY RISK	M	D X	L X	T X	A =	F

**Step 3:** Compute Adjusted Building Status (R) - Use Table 2.

- A. If building is classified as "NEW" use Table 3A. If building is classified as "Existing" use Table 3B.
- B. Transfer the value of F from Table 2 to Table 3A or Table 3B as appropriate. Calculate R.
- C. Transfer R to the block labeled R in Table 7 on page 4 of the work sheet.

TABLE 3A. (NEW BUILDINGS)	TABLE 3B. (EXISTING BUILDINGS)
F R	FR
1.0 X =	0.6 X =

\* FIRE/SMOKE ZONE is a space separated from all other spaces by floors, horizontal exits, or smoke barriers.

SURVEYOR SIGNATURE	TITLE	DATE
FIRE AUTHORITY SIGNATURE	TITLE	DATE

Step 4: Determine Safety Parameter Values - Use Table 4.

A. Select and circle the safety value for each safety parameter in Table 4 that best describes the conditions in the zone. Choose only one value for each of the 13 parameters. If two or more appear to apply, choose the one with the lowest point value.

				TABLE	- 4.					
Safety Parameters				Safe	ety Param	neters Va	alues			
1. Construction				ombustible s III, IV, and V				NonCombustible Types I and II		
Floor or Zone				200	211 + 2HH		000	111	222, 322, 43	
First	-2	0		-2	0		0	2	2	
Second	-7	-2		-4	-2		-2	2	4	
Third	-9	-7		-9	-7	7	-7	2	4	
4th and Above	-13	-7		-13	-7	7	-9	-7	4	
2. Interior Finish (Corridors and Exits)	Class C -5(0) <sup>f</sup>		Class B 0(3) <sup>f</sup>		Clas 3					
3. Interior Finish (Rooms)	Class C -3(1) <sup>f</sup>		Class B 1(3) <sup>f</sup>		Clas		_			
. ,		to	<1/2 hour		-			>1 bour		
4. Corridor Partitions/Walls	None or Incomple -10(0) <sup>a</sup>	le	<'/2 hour 0		<u>≥¹/₂ to &lt;</u> 1(0		_	≥1 hour 2(0) <sup>a</sup>		
5. Doors to Corridor	No Door		<20 min FPR			,		min FPR and Auto Clos.		
	-10			IX	≥20 min FPR 1(0) <sup>d</sup>			2(0) <sup>d</sup>		
6. Zone Dimensions		Dead End					No Dea	d Ends >30 ft and	Zone Length Is	
	>100 ft >50 ft to 100 f			t 30 ft to 50 ft		>15	>150 ft 100 ft to 150			
	-6(0) <sup>b</sup>	-4(0	-4(0) <sup>b</sup>		-2(0) <sup>b</sup> -2(0)		0) <sup>c</sup>	0	1	
7. Vertical Openings	Open 4 or More	Open 4 or More Open 2 or 3		3		En	closed witl	n Indicated Fire R	esist.	
, ,	Floors		Floors		<1	hr	<u>≥</u> 1	hr to <2 hr	<u>&gt;</u> 2 hr	
	-14		-10		С	)		2(0) <sup>e</sup>	3(0) <sup>e</sup>	
8. Hazardous Areas	Double Deficiency				Single	Deficiency	/	No Deficiencies		
	In Zone	0	Outside Zone		In Zone		In A	djacent Zone		
	-11		-5		-6			-2	0	
9. Smoke Control	No Control		noke Barr erves Zor			Mech. Ass by	sisted Syst / Zone	ems		
	-5(0) <sup>c</sup>	-5(0) <sup>c</sup> 0								
10. Emergency	<2 Routes					Multip	le Routes	·		
Movement Routes			Deficient		W/O Horizontal Exit(s)			Horizontal Exit(s)	Direct Exit(s)	
	-8		-2		0			1	5	
11. Manual Fire Alarm	No Mar	ual Fire Al	larm		Manual Fire Alarm			m		
					W/O F.	D. Conn.	V	V/F.D. Conn		
		-4				1		2		
12 Smoke Detection and Alarm	None	c	orridor Or	nly	Room	ns Only	s Only Corridor a		Total Spaces In Zone	
	0(3) <sup>g</sup>		2(3) <sup>g</sup>			(3) <sup>g</sup>		4	5	
13. Automatic Sprinklers	None		Corridor an		Entire Building					
	0		8		10		$\neg$			

**NOTE:** <sup>a</sup> Use (0) where parameter 5 is -10.

<sup>b</sup> Use (0) where parameter 10 is -8.

- <sup>c</sup> Use (0) on floor with fewer than 31 patients (existing buildings only)
- <sup>d</sup> Use (0) where parameter 4 is -10.

For SI units: 1 ft = 0.3048 m

<sup>e</sup> Use (0) where Parameter 1 is based on first floor zone or on an unprotected type of construction (columns marked "000" or "200")

<sup>f</sup> Use ( ) if the area of Class B or C interior finish in the corridor and exit or room is protected by automatic sprinklers and Parameter 13 is 0; use ( ) if the room with existing Class C interior finish is protected by automatic sprinklers, Parameter 4 is greater than or equal to 1, and Parameter 13 is 0.

<sup>g</sup> Use this value in addition to Parameter 13 if the entire zone is protected with quick-response automatic sprinklers.

Step 5: Compute Individual Safety Evaluations – Use Table 5.

- A. Transfer each of the 13 circled Safety Parameter Values from Table 4 to every unshaded block in the line with the corresponding Safety Parameter in Table 5. For Safety Parameter 13 (Sprinklers) the value entered in the People Movement Safety column is recorded in Table 5 as 1/2 the corresponding value circled in Table 4.
- B. Add the four columns, keeping in mind that any negative numbers deduct.
- C. Transfer the resulting total values for S<sub>1</sub>, S<sub>2</sub>, S<sub>3</sub>, S<sub>G</sub> to blocks labeled S<sub>1</sub>, S<sub>2</sub>, S<sub>3</sub>, S<sub>G</sub> in Table 7 on page 4 of this sheet.

TABLE 5. INDIVIDUAL SAFETY EVALUATIONS								
Safety Parameters	Containment Safety (S1)	Extinguishment Safety (S₂)	People Movement Safety (S <sub>3</sub> )	General Safety (S₄)				
1. Construction								
2. Interior Finish (Corr. and Exit)								
3. Interior Finish (Rooms)								
4. Corridor Partitions/Walls								
5. Doors to Corridor								
6. Zone Dimensions								
7. Vertical Openings								
8. Hazardous Areas								
9. Smoke Control								
10. Emergency Movement Routes								
11. Manual Fire Alarm								
12. Smoke Detection and Alarm								
13. Automatic Sprinklers			÷ 2 =					
Total Value	S1=	S2=	S3=	S4=				

TABLE 6. MANDATORY SAFETY REQUIREMENTS (FOR USE IN HOSPITALS OR NURSING HOMES)							
Containment Extinguishment Peopl (Sa) (Sb)						e Movement (Sc)	
Zone Location	New	Exist.	New	Exist.	New	Exist.	
1 <sup>st</sup> story	11	5	15(12) <sup>a</sup>	4	8(5) <sup>a</sup>	1	
2 <sup>nd</sup> or 3rd story <sup>b</sup>	15	9	17(14) <sup>a</sup>	6	10(7) <sup>a</sup>	3	
4 <sup>th</sup> story or higher	18	9	19(16) <sup>a</sup>	6	11(8) <sup>a</sup>	3	

a. Use ( ) in zones that do not contain patient sleeping rooms.

b. For a 2<sup>nd</sup> story zone location in a sprinklered EXISTING facility, as an alternative to the mandatory safety requirement values set specified in the table, the following mandatory values *set* shall be permitted to be used: Sa=7, Sb=10, and Sc=7

- Step 6: Determine Mandatory Safety Requirement Values Use Table 6.
  - A. Using the classification of the building (i.e., New or Existing) and the floor where the zone is located circle the appropriate value in each of the three columns in Table 6.
  - B. Transfer the three circled values from Table 6 to the blocks marked  $S_a$ ,  $S_b$ , and  $S_c$  in Table 7.
  - C. For each row check "Yes" if the value in the answer block is zero or greater. Check "No" if the value in the answer block is a negative number.

	TABLE 7. ZONE FIRE SAFETY EQUIVALENCY EVALUATION							
Containment Safety (S1)	minus	Mandatory Containment (S <sub>s</sub> )	≥ 0	$ \begin{bmatrix} S_1 \\ - \end{bmatrix} \begin{bmatrix} S_a \\ - \end{bmatrix} \begin{bmatrix} C \\ - \end{bmatrix} $				
Extinguishment Safety (S <sub>2</sub> )	minus	Mandatory Extinguishment (S₀)	≥ 0					
People Movement Safety (S <sub>3</sub> )	minus	Mandatory People Movement (S <sub>c</sub> )	≥ 0	$ \begin{array}{c} S_3 \\ \hline \end{array} - \begin{array}{c} S_c \\ \hline \end{array} \end{array} = \begin{array}{c} P \\ \hline \end{array} $				
General Safety (S₄)	minus	Occupancy Risk (R)	≥ 0					

	TABLE 8. FACILITY FIRE SAFETY REQUIREMENTS WORKSHEET	Г		
	mplete one copy of this worksheet for each facility. r each consideration, select and mark the appropriate column.	Met	Not Met	Not Applic.
Α.	Building utilities conform to the requirements of Section 9.1.			
В.	In new facilities only, life-support systems, alarms, emergency communication systems, and illumination of generator set locations are powered as prescribed by 18.5.1.2 and 18.5.1.3.			
C.	Heating and air conditioning systems conform with the air conditioning, heating, and ventilating systems requirements within Section 9.2, except for enclosure of vertical openings, which have been considered in Safety Parameter 7 of Worksheet 4.7.6.			
D.	Fuel-burning space heaters and portable electrical space heaters are not used.			
Ε.	There are no flue-fed incinerators.			
F.	An evacuation plan is provided and fire drills conducted in accordance with 18.7.1/18.7.2 and 19.7.1/19.7.2.			
G.	Smoking regulations have been adopted and implemented in accordance with 18.7.4 and 19.7.4.			
H.	Draperies, upholstered furniture, mattresses, furnishings, and decoration combustibility is limited in accordance with 18.7.5 and 19.7.5.			
Ι.	Fire extinguishers are provided in accordance with the requirements of 18.3.5.4 and 19.3.5.6.			
J.	Exit signs are provided in accordance with the requirements of 18.2.10.1 and 19.2.10.			
К.	Emergency lighting is provided in accordance with 18.2.9.1 or 19.2.9.			
L.	Standpipes are provided in all new high rise buildings as required by 18.4.2.			

## CONCLUSIONS

1. All of the checks in Table 7 are in the "Yes" column. The level of fire safety is at least equivalent to that prescribed by the *Life Safety Code*.\*

2. One of more of the checks in Table 7 are in the "No" column. The level of fire safety is not shown by this system to be equivalent to that prescribed by the *Life Safety Code*.\*

\*The equivalency covered by this worksheet includes the majority of considerations covered by the *Life Safety Code*. There are a few considerations that are not evaluated by this method. These must be considered separately. These additional considerations are covered in Table 8, the "Facility Fire Safety Requirements Worksheet." One copy of this separate worksheet is to be completed for each facility.

According to the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number. The valid OMB control number for this information collection is 0938-0242. The time required to complete this information collection is estimated to average 5 minutes per response, including the time to review instructions, search existing data resources, gather the data needed, and complete and review the information collection. If you have any comments concerning the accuracy of the time estimate(s) or suggestions for improving this form, please write to: CMS, Attn: PRA Reports Clearance Officer, 7500 Security Boulevard, Baltimore, Maryland 21244-1850.

## FIRE SAFETY SURVEY REPORT CRUCIAL DATA EXTRACT (TO BE USED WITH CMS-2786 FORMS)

PR	PROVIDER NUMBER FACILITY NAME					,	SURVEY DATE		
K1							* K4		
K6 DATE OF PLAN APPROVAL				K3 MULTIPLE CONSTRUCTION A   TOTAL NUMBER OF BUILDINGS E					
	,		NUMBER OF THIS I				C FLOOR D APARTMENT UNIT		
LSC	C FOR	M INDICATOR					ED UNDER CHAPTER 21		
[		Health	Care Form		SMALL	(16 BEDS OR LES	S)		
	12	2786R	2000 EXISTING			1 PROMPT			
	13	2786R	2000 NEW		К8:	2 SLOW 3 IMPRACTICAL			
[		AS	SC Form		LARGE				
	14	2786U	2000 EXISTING						
	15	2786U	2000 NEW			4 PROMPT			
		I			K8:	5 SLOW			
		ICF/	MR Form			6 IMPRACTICAL			
	16	2786V, W, X	2000 EXISTING		APARTMENT	HOUSE			
	17	2786V, W, X	2000 NEW			7 PROMPT			
-					K8:	8 SLOW			
* K7		SELECT NUMBE	R OF FORM USED FROM	1 ABOVE		9 IMPRACTICAL			
•		K29 or K56 are 86 M, R, T, U, V,	marked as not applicable W, X and Y.)	)	ENTER E – SO	CORE HERE			
	K2	29:	K56:		К5:	e.g. 2.5			
*K9:	FACIL	ITY MEETS LS	C BASED ON (Check al	that appl	y)				
	A	.1.	A2.	A3		A4.	A5.		
		(COMP. WITH L PROVISIONS)	(ACCEPTABLE POC)	(	(WAIVERS)	(FSES)	(PERFORMANCE BASED DESIGN)		
FAC	CILITY		ET LSC	K0180 A		В.	C.		
	B			-	SPRINKLERED areas are sprinklered)	PARTIALLY SPRINK (Not all required areas are			
* M	ANDA	TORY							